

U2120-O-HSP



Catalog Number	U2120-O-HSP
Marketing Product Description	7 Terminal Ringless Plain Top Lever Bypass Stainless Steel Hasp
UPC	784572292550
Length (IN)	6.5
Width (IN)	17.75
Height (IN)	31.75
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	320 Continuous Ampere
Phase	3 Phase
Frequency Rating	60 Hertz
Size	6.5L x 17.75W x 31.75H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Underground
Terminal	3/8 Inch Stud
Insulation	Glass Polyester
Mounting	Surface Mount

Enclosure G90 Galvanized Steel with Powder Coat Finish

Jaw Quantity 7 Terminal

Bypass Type Lever Bypass

Number of Meter Positions 1 Position

Equipment Ground Grounding Stud

Hub Opening Plain Top

Number Of Receptacles 0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.