



MILBANK
ENERGY AT WORK

U5885-X-KK-K2-ALT



Catalog Number	U5885-X-KK-K2-ALT
Marketing Product Description	4 Terminal Ringless Large Closing Plate Horn Bypass 5 Position 5-200 Ampere Main Breaker Provision Double Connector 6-350kcmil Alliant Energy
UPC	784572535183
Length (IN)	5.125
Width (IN)	51.063
Height (IN)	30
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket With Main
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.125L x 51.063W x 30H
Number Of Cutouts	0
Cutout Size	Breaker Provision
Cable Entry	Overhead or Underground
Terminal	Double Mechanical

Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	5 Positions
Equipment Ground	Ground Lug
Hub Opening	Large Closing Plate
Line Side Wire Range	Two 6 AWG - 350 kcmil
Number Branch Circuits	5
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.