



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series low voltage cylindrical fuse

C14M40

UPC:051712754736

Dimensions:

- **Height:** 51 MM
- **Length:** 51 MM
- **Width:** 14.3 MM

Weight:51 G

Warranties:

- 1 year limited

Specifications:

- **Type:** fuse
- **Application:** motor protection | for industrial applications
- **Voltage Rating:** 500V
- **Voltage Rating Numeric:** 500 V
- **Amperage Rating:** 40A
- **Amperage Rating Numeric:** 40 A
- **Class:** Class aM
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 14 x 51 mm
- **Material Type:** Ceramic body, Silver-plated copper endcap
- **Mounting:** 14 x 51 mm CH Modular fuse holder
- **Packaging Type:** Standard
- **Quantity:** 10 per package
- **Fuse Indicator:** CH14 fuse holder
- **Fuse Type:** Cylindrical
- **Breaking Capacity:** 120 KA
- **Frequency Rating Maximum:** 45 HZ
- **Frequency Rating Minimum:** 62 HZ
- **Fuse Shape:** cylindrical
- **Release Characteristic:** Other
- **Utilization Category:** aM (switchgear)



protection)

- **Voltage Type:** AC
- **With Striker:** No

Supporting documents:

- [Product Catalog](#)

Certifications:

- IEC 60269
- VDE

Product compliance:

- Contact factory
- CE Marked
- GoST-R
- RoHS Compliant