



Main

Range of Product	Twido
Accessory / separate part category	Connection accessories
Accessory / Separate Part Type	Tap isolation box
Accessory / separate part designation	Tap isolation box
Accessory / separate part destination	RS485 serial link
Product Specific Application	Lines prepolarised (2 R 620 Ohm) RS485 line isolation Line end adaptor (RC 120 Ohm, 1 nF)

Complementary

Range Compatibility	Twido programmable controller Modicon M238 logic controller
[Us] rated supply voltage	24 V
Supply circuit type	DC
Supply	External
Electrical connection	1 screw terminal block 2 connectors RJ45 for tap-off)
Mounting Support	35 mm symmetrical DIN rail
Net Weight	0.22 lb(US) (0.1 kg)

Ordering and shipping details

Category	22531-PLCS, TWIDO, TWD
Discount Schedule	PC12
GTIN	3595863895360
Nbr. of units in pkg.	1
Package weight(Lbs)	5.50 oz (156.0 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.60 in (6.6 cm)
Package 1 width	2.56 in (6.5 cm)
Package 1 Length	4.72 in (12 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Weight	9.24 lb(US) (4.191 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Contractual warranty

Warranty	18 months
----------	-----------