

XMLG001D21

Electronic pressure sensors, Pressure sensors XM, sensor XMLG, 0...1 bar, G 1/4 A (male), 24 V, 4...20 mA, set of 1

Main

Range of Product	Telemecanique Pressure sensors XM
Product or Component Type	Electronic pressure sensors
Pressure sensor type	Pressure transmitter
Pressure sensor name	XMLG
Pressure Rating	14.5 psi (1 bar)
Fluid connection type	G 1/4A (male) DIN 3852-E
Controlled fluid	Air 5...257 °F (-15...125 °C)) Corrosive fluid 5...257 °F (-15...125 °C)) Hydraulic oil 5...257 °F (-15...125 °C)) Fresh water 32...257 °F (0...125 °C))
Type of output signal	Analogue
Analogue output function	4...20 mA, 2 wires
Electrical connection	1 male connector M12, 3 pins
[Us] rated supply voltage	12 V DC 8...33 V) 24 V DC 8...33 V)
Quantity per Set	Set of 1
Type of Packing	Individual
Diameter	0.9 in (22.8 mm)

Complementary

Pressure setting range	0.0000000000...14.5 psi (0...1 bar)
Maximum permissible accidental pressure	39.2 psi (2.7 bar)
Destruction pressure	43.5 psi (3 bar)
Local display	Without
Electrical circuit type	Control circuit
Current consumption	< 20 mA
Materials in contact with fluid	Ceramic FPM (Viton) Stainless steel type AISI 303
Operating position	Any position
Protection Type	Load short-circuit Reverse polarity
Surge withstand	1 KV 42 Ohm IEC 61000-4-5 500 kV 12 Ohm IEC 61000-4-5
[Uimp] rated impulse withstand voltage	0.5 kV
Response time on output	< 2 ms
Drift of the sensitivity	+/- 0.015 % of measuring range/°C
Drift of the zero point	+/- 0.015 % of measuring range/°C
Measurement accuracy	+/- 0.3 % of the measuring range
Repeat accuracy	+/- 0.1 % of the measuring range
Mechanical durability	10000000 cycles
Net Weight	0.209 lb(US) (0.095 kg)
Height	2.3 in (58.1 mm)
Length	1.9 in (48.5 mm)
Scale type	Fixed differential

Environment

Standards	CE IEC 61326-2-3
Product Certifications	CSA C22.2 No 14[RETURN]UL 508
Protective treatment	TC
Ambient Air Temperature for Operation	5...185 °F (-15...85 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Vibration resistance	20 gn 9...2000 Hz)IEC 60028-2-6
Shock resistance	25 gn 11 ms IEC 60068-2-27
Resistance to electrostatic discharge	15 kV in air IEC 61000-4-2 8 kV on contact IEC 61000-4-2
Resistance to electromagnetic fields	182.9 V/m (200 V/m) 80...1000 Hz IEC 61000-4-3
Resistance to fast transients	4 kV IEC 61000-4-4
Resistance to conducted disturbances	30 V 0.15...80 Hz)IEC 61000-4-6
Resistance to magnetic fields	98.4 A/m (30 A/m) 50 Hz IEC 61000-4-8
IP degree of protection	IP66 conforming to IEC 60529 IP67 conforming to IEC 60529
NEMA Degree of Protection	NEMA 4

Ordering and shipping details

Category	US10DS221551
Discount Schedule	0DS2
GTIN	3389110969511
Returnability	No
Country of origin	CH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.000 cm)
Package 1 Width	4.13 in (10.500 cm)
Package 1 Length	5.31 in (13.500 cm)
Package 1 Weight	4.727 oz (134.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	4.248 lb(US) (1.927 kg)

Offer Sustainability

SCIP Number	63bf6aac-e7ba-4853-b69a-9632a64b72b3
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------