

CableTrak Kits less Brackets, 1', 101 Series

By Hubbell Wiring Device-Kellems
Catalog # [HCT101141](#)

CableTrak Kits less Brackets, 1', 101 Series



Application

- Cable and Hose Carrier

Performance

- Environmental - Max. Operating Speed - 600 FPM (feet per minute), 180 MPM (meters per minute).
- Environmental - Max. Unsupported Travel Distance - HCT16 Series without sag 9 ft. (2.8 m) with sag 10.5 ft. (3.2 m)
- HCT25 Series without sag 13.5 ft. (4.1 m) with sag 17 ft. (5.2 m)
- Environmental - Operating Temperature - Continuous +20°F to +100°F (-7°C to 38°C)
- Intermittent* -40°F to +220°F (-40°C to 104°C).

General

Catalog Number	HCT101141
Color	Black
EU RoHS Indicator	No
Item Type	CableTrak Extender Kit
Material	Nylon, Fiberglass Reinforced
OEM Brand Name	Hubbell Wiring Device-Kellems
Specifications	- Applications - Machine tool, robotic automation, material handling - Material - Fiberglass reinforced nylon

UPC783585343303

Dimensions

Depth	0.75
Display Size	Standard Sized
Width	0.59 in

Electrical Ratings

ConnectivitySnap Together Sections

Conductor Related

Wire Size.531"

Logistics

Carton Quantity6

Product Assets

[Brochures - POWERTRAK® GRP Non-Metallic Cable/Hose Carrier](#)
[Catalog Page - WDK I-10 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Installation Manuals - WIRING_PD1465_INSTALLINST](#)
[Sales Drawings - WDK_HCT101141_DRAWING_PDF](#)
[Specifications - HCT101141](#)
[Warranty - Industrial & Commercial Products](#)