



Main

Enclosure type	Open box
----------------	----------

Complementary

Line Rated Current	10 A
Approximate adjustable differential	0.4...1.5 psi (2.76...10.34 kPa)
Controlled fluid	Hydraulic oil Non-corrosive gas Non-corrosive liquids Air
Fluid connection type	0.25 inch 18 NPTF
Local display	Without
Locking options description	Without keylocks
Material	Zinc plated steel flange
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	100 psig
Maximum operating rate	120 cyc/mn
Permissible voltage	600 V
Pilot light	Without pilot lamp
Pressure actuator	Diaphragm
Range on decreasing pressure	0.2...10 psi (1.38...68.95 kPa)
Repeat accuracy	+/- 0.1...1 %
Scale type	Adjustable differential
Stage of operation	Stage 1
Switch function	SPDT non-isolated
Switching threshold drift	+/- 1 % adjustable range over 1000000 operations
Temperature of controlled fluid	-40...250 °F (-40...121 °C)
Type of setting	Fixed

Environment

Ambient air temperature for operation	-10...185 °F (-23...85 °C)
NEMA degree of protection	No enclosure rating (open device) Not rated (open device)
Product certifications	CSA LR25490 class 3211 03 UL Listed CSA CE
Shock resistance	50 gn
Standards	UL 508 IEC 60957-5-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	21522 - 9012 G INDUSTRIAL PRESSURE SWITCHES
Discount Schedule	CP7G
GTIN	00785901348764
Nbr. of units in pkg.	1
Package weight(Lbs)	2 lb(US) (0.91 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	8.89 in (22.581 cm)
Package 1 width	3.50 in (8.890 cm)
Package 1 Length	22.58 in (57.355 cm)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------