



YDS301AT, Aluminum Full Tension Sleeve

By Burndy
Catalog # [YDS301AT](#)



Hysplice, 336.4 (19, 37), 9-7/8 in L, Full Tension Sleeve for All Aluminum Compressed and Compact Conductors.

Application

For All Aluminum Compressed And Compact Conductors

General

Connector Type	Splice
Die Index	321
EU RoHS Indicator	Yes
Insulation	Y
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS-AT
UPC	781810015902
UPC 12 Digit	7818100159022

Dimensions

Dimension - B Length fraction	4-22/25 in
Dimension - B Length inch	4.88 in
Dimension - L Length Overall mm	251 mm
Dimension - Length Overall inch	9.88 in
Dimension - Outside Diameter inch	1.06 in

Conductor Related

Conductor - ACSR Cmpt Size	336.4
Conductor - ACSR Cmpt Size Range	336.4
Conductor - ACSR Str Size	336.4 (18/1) Merlin;336.4 (26/7) Linnet;336.4 (30/7) Oriole
Conductor - ACSR Str Size Range	336.4 (18/1) Merlin-336.4 (30/7) Oriole
Conductor - AL Str Size	336.4
Conductor - AL Str Size Range	336.4
Conductor Type	• ACSR C Str-Size • AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	30
Minimum Pack Quantity	1
Pallet Quantity	2700

Product Assets

[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - SD..021880-01](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-YDS301AT-SPEC-EN | REV 8/2023