



YGLR34C34 Compression Ground Rod Connector

By Burndy

Catalog # [YGLR34C34](#)



Copper Compression Connector, Ground Rod to Grid, 250 kcmil - 500 kcmil, 3/4" Ground Rod.

Features

- Ground grid connector for a range of copper cable to ground rod
- Provides high torque strength on ground rod
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth And Concrete

General

Catalog Number	YGLR34C34
Connector Type	Tap
Die Index	1011
Die Index - Element A	1011
Die Index - Element B	1011
EU RoHS Indicator	Yes
Material	Copper
Oxide Inhibitor Type	Penetrox E
Physical Attribute - Number of	2
Crimps Required	
Plated	N
Plating Type	Unplated
Precrimp Die	UPRECRIMP34
Prefilled Oxide Inhibitor	Y
Sub Brand	GRIDLOK
Trade Name	GRIDLOK™
Type	Taps
UPC	781810220856
UPC 12 Digit	7818102208566

Dimensions

Dimension - B Length fraction	3/4 in
Dimension - B Length inch	0.75 in
Dimension - D inch	0.50 in
Dimension - Ground Rod Size	3/4
Dimension - Height mm	0 mm
Dimension - L Length Overall mm	67 mm
Dimension - Length BB inch	0.88 in
Dimension - Length Overall inch	2.63 in

Conductor Related

Conductor - Copper Str Size A	250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Size A Range	250 kcmil-500 kcmil
Conductor - Rebar Tap	5;6
Conductor - Rod Size B	3/4 in
Conductor - Rod Size B Range	3/4 in
Conductor Type	• CU C Str-Size • Rod-Size • CU Weld C Str-Size

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	• UL467 • IEEE 837 • IEEE 837 2014 Qualified
Standards - Industry Standards Met	UL467;IEEE 837;IEEE 837 2014 Qualified
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Carton Quantity	6
Minimum Pack Quantity	1
Pallet Quantity	1440

Product Assets

[3D Models - YGLR34C34_MODEL-PDF](#)

[3D Models - YGLR34C34_MODEL-STEP](#)

[3D Models - YGLR34C34_MODEL-IGES](#)

[Catalogs - BURNDY Master Catalog - Section E1 - Compression Grounding](#)

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)



A Hubbell brand