



GD1626, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy
Catalog # [GD1626](#)



Mechanical Grounding Connector, 2 Parallel Cables to Rod or Pipe; Accommodates: #4 AWG (Sol.) - 2/0 AWG (Str.); 1-3/8" to 1-1/2" Rod, 1-1/4" Pipe; #6 DURIUM Silicon Bronze U-Bolt, Hex Nuts, and Split Lockwasher

Application

For Joining A Range Of Two Parallel Cables To Rod Or Tube, Grounding Fence Posts, Direct Burial Applications In Earth Or Concrete

General

EU RoHS Indicator	Yes
Installation Torque	240 LBS/in
Recommended in-lb	
Material	Copper Alloy, Cast
Material Type - Screw	DURIUM™ Silicon Bronze
Plated	N
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Type	GD
U Bolt Type	204
UPC	781810260272
UPC 12 Digit	7818102602722

Dimensions

Dimension - B Length inch	1.25 in
Dimension - Height fraction	3-1/2 in
Dimension - Height inch	3.50 in
Dimension - Width fraction	3 in
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm

Conductor Related

Conductor - Copper Solid Size	4;3;2;1;0;2/0
Conductor - Copper Solid Size Range	4-2/0
Conductor - Copper Str Size	4;3;2;1;0;2/0
Conductor - Copper Str Size B Range	1.25
Conductor - Copper Str Size Range	4-2/0
Conductor - Copper Tube Std Size	1-1/4
Conductor - Copper Tube Std Size Range	1-1/4
Conductor - Rod Size	1 1/2 in
Conductor - Rod Size Range	1 1/2 in

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[3D Models - GD1626_MODEL-PDF](#)
[3D Models - GD1626_MODEL-IGES](#)
[3D Models - GD1626_MODEL-STEP](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - SD..013775-01](#)





A proud member of the Hubbell Family.