

# GD1926, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy  
Catalog # [GD1926](#)



Mechanical Grounding Connector, 2 Parallel Cables to Rod or Pipe, 4 AWG ( Sol.) - 2/0 AWG (Str.), 2-1/2" to 2-7/8" Rod, 2-1/2" Pipe.

### Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

### Application

For Joining A Range Of Two Parallel Copper Cables To Rod Or Pipe And Burial In Ground Or Concrete

### General

|                       |                        |
|-----------------------|------------------------|
| Catalog Number        | GD1926                 |
| EU RoHS Indicator     | Yes                    |
| Installation Torque   | 240 LBS/in             |
| Recommended in-lb     |                        |
| Material              | Copper Alloy, Cast     |
| Material Type - Screw | DURIUM™ Silicon Bronze |
| Plated                | N                      |
| Plating Type          | Unplated               |
| Sub Brand             | MECHANICAL CONNECTOR   |
| Type                  | GD                     |
| U Bolt Type           | 266                    |
| UPC                   | 781810260364           |
| UPC 12 Digit          | 7818102603644          |

### Dimensions

|                             |          |
|-----------------------------|----------|
| Dimension - B Length inch   | 1.38 in  |
| Dimension - Height fraction | 5 in     |
| Dimension - Height inch     | 5.00 in  |
| Dimension - Height mm       | 127 mm   |
| Dimension - Width fraction  | 4-1/4 in |
| Dimension - Width inch      | 4.19 in  |
| Dimension - Width mm        | 106 mm   |

### Conductor Related

|                                     |                 |
|-------------------------------------|-----------------|
| Conductor - Copper Solid Size       | 4;3;2;1;1/0;2/0 |
| Conductor - Copper Solid Size Range | 4-2/0           |

|                                        |                 |
|----------------------------------------|-----------------|
| Conductor - Copper Str Size            | 4;3;2;1;1/0;2/0 |
| Conductor - Copper Str Size B Range    | 2.5             |
| Conductor - Copper Str Size Range      | 4 AWG - 2/0 AWG |
| Conductor - Copper Tube Std Size       | 2-1/2           |
| Conductor - Copper Tube Std Size Range | 2-1/2           |
| Conductor - Rod Size                   | 2 1/2 in        |
| Conductor - Rod Size Range             | 2 1/2 in        |

### Certifications And Compliance

|                                         |       |
|-----------------------------------------|-------|
| Buy American Compliant                  | Yes   |
| Certification - CSA Approved            | No    |
| Certification - ETL                     | No    |
| Certification - UL Listed Direct Burial | Yes   |
| Certification - UL Recognized           | No    |
| Certification - cULus                   | No    |
| Industry Standard(s)                    | UL467 |
| Standards - Industry Standards Met      | UL467 |
| Standards - RoHS Compliance Status      | EX    |
| UL Listed                               | Yes   |

### Logistics

|                       |   |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

### Product Assets

[Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_gdla](#)  
[Sales Drawings - SD..013775-01](#)  
[Specifications - GD1926](#)