



CT250500RQ0, Cable Tie, 250 Lb Tensile, UV Black, Releasable

By Burndy
Catalog # [CT250500RQ0](#)

Nylon 6/6 Standard Releasable Cable Tie, UV Black, 250 Lbs Min
Ten Strgth, 20.00" L, 0.50" W.

Features

Releaseable

Application

For Use Where Service Requires Adding Or Subtracting Wires
From An Existing Wire Bundle

General

Catalog Number	CT250500RQ0
Color	Black
EU RoHS Indicator	Yes
Material	NYLON 6/6
Operating Temperature Celcius Max	85 °C
Operating Temperature Celcius Min	-40 °C
Rating - Minimum Tensile Strength lbs	250
Sub Brand	UNIRAP,CABLE TIE
Trade Name	UNIRAP™
Type	Heavy Duty Releasable
UPC	781810334836

Dimensions

Dimension - Bundle Diameter Max inch	6
Dimension - L Length Overall mm	559 mm



Dimension - Length Overall inch	22 in
Dimension - Width inch	0.50 in
Dimension - Width mm	13 mm

Certifications And Compliance

Buy American Compliant	Yes
Certification - 94V0 Rated	N
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - UV Rated	Yes
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	500
Minimum Pack Quantity	25

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section G - Wire Management](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_CT_UNIRAP_REL_CABLETIE_LineArt](#)
- [Sales Drawings - 50034347](#)
- [Specifications - CT250500RQ0](#)



A Hubbell brand