



QPX282C, Heavy Duty Copper Tapping Connector, Run: 1-4/0, Tap: 6-2 AWG

By Burndy
Catalog # [QPX282C](#)



VERSITAP™ Mechanical Parallel Clamp for Copper;
Accommodates: Run: #1 - 4/0 AWG; Tap: #6 - #2 AWG.

Application

For Tee, Cross, Parallel, Butt And Tap Connections, Copper

General

Connector Type	Universal Clamp
EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	180 LBS/in
Material	Copper
Material - Hardware	DURIUM™ Silicon Bronze
Physical Attribute - Number of Screws	2
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Plating Type	Unplated
Sub Brand	VERSITAP
Temperature Rating	194
Trade Name	VERSITAP™
Type	QPX
UPC	781810342008
UPC 12 Digit	7818103420088

Dimensions

Dimension - Height fraction	2-1/16
Dimension - Height inch	2.06
Dimension - L Length Overall mm	33 mm
Dimension - Length Overall inch	1.31 in
Dimension - Width fraction	1-9/16 in
Dimension - Width inch	1.56
Dimension - Width mm	40 mm

Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

Conductor Related

Conductor - Copper Str Run	1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Run Range	1 AWG-4/0 AWG
Conductor - Copper Str Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Str Tap Range	6 AWG-2 AWG
Conductor Type	• CU C Str-Run • CU C Str-Tap

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - sa007887-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-QPX282C-SPEC-EN | REV 3/2024

