



Tin Plated Heavy Duty Copper Tapping Connector

By Burndy
Catalog # [QPX2828Y](#)

VERSITAP™ Mechanical Parallel Clamp for Copper and Aluminum; Run: 1/0 - 4/0 Str; Tap: 1/0 - 4/0 Str; 2" Length; 2-1/8" Width



Application

For Use With Copper Or Aluminum Cable

General

Connector Type	Universal Clamp
EU RoHS Indicator	Yes
Installation Torque	250 LBS/in
Recommended in-lb	
Material	Copper
Material - Hardware	DURIUM™ Silicon Bronze
Plated	Y
Plating Type	Tin
Sub Brand	VERSITAP
Trade Name	VERSITAP™
Type	QPX-Y, Universal
UPC	781810342404

Dimensions

Dimension - Height fraction	2 in
Dimension - Height inch	2.00 in
Dimension - L Length Overall mm	51 mm
Dimension - Length Overall inch	2.00 in
Dimension - Width fraction	2-1/8 in
Dimension - Width inch	2.14 in
Dimension - Width mm	54 mm

Conductor Related

Conductor - AL Str Run	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - AL Str Run Range	1/0 AWG-4/0 AWG
Conductor - AL Str Tap	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - AL Str Tap Range	1/0 AWG-4/0 AWG
Conductor - Copper Str Run	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Run Range	1/0 -4/0 AWG
Conductor - Copper Str Tap	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Tap Range	1/0 -4/0 AWG
Conductor Type	- AL C Str-Run - CU C Str-Run - AL C Str-Tap - CU C Str-Tap

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[3D Models - QPX2828Y_MODEL-IGES](#)
[3D Models - QPX2828Y_MODEL-STEP](#)
[3D Models - QPX2828Y_MODEL-PDF](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - sd..026550](#)



