

YCA26R2N, Al compression Lug, 2-Hole, 1/2" Stud, 1-3/4" Spacing, 2/0

By Burndy

Catalog # [YCA26R2N](#)

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.30 IN L.

Application

For ACSR/6201/5005 (Compressed/Compact), Aluminum

General

Catalog Number	YCA26R2N
Connector Type	Terminal
Die Index	245;9A
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	TERMINAL,TERMINALS
Type	YCA-R-N, Terminal
UPC	781810810439
UPC 12 Digit	7818108104399

Dimensions

Dimension - B Length inch	2.43 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	160 mm
Dimension - Length Overall inch	6.30 in
Dimension - Outside Diameter inch	0.70 in
Dimension - Pad Width inch	0.97 in



Conductor Related

Conductor - ACSR Str Size	2/0 (6/1) Quail AWG
Conductor - ACSR Str Size Range	2/0 (6/1) Quail AWG
Conductor - AL Str Size	2/0 AWG
Conductor - AL Str Size Range	2/0 AWG

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	25
Minimum Pack Quantity	1
Pallet Quantity	9800

Product Assets

[Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_YCA_LineArt](#)
[Sales Drawings - SD..029515-01](#)
[Specifications - YCA26R2N](#)