



YDS4W, Copper, Single Sleeve Full Tension Splice

By Burndy
Catalog # [YDS4W](#)

HYSPLICE Single Sleeve Full Tension Splice, Accommodates Wire: #4 Cu Sol (Hard, Medium, or Soft Drawn), Die Index: 162, Made of copper tubing, Installed with standard tools and dies.

Application

For Solid Copper Conductors

General

Catalog Number	YDS4W
Connector Type	Splice
Die Index	162
EU RoHS Indicator	Yes
Material	Copper
Physical Attribute - Number of Crimps Required	4
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS
UPC	781810820940

Dimensions

Dimension - B Length inch	1.15 in
Dimension - L Length Overall mm	65 mm
Dimension - Length Overall inch	2.55 in
Dimension - Outside Diameter inch	0.38 in

Conductor Related

Conductor - Copper Solid Size	4 AWG
Conductor - Copper Str Size	6 AWG - 3 AWG



Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	100
Minimum Pack Quantity	1
Pallet Quantity	23200

Product Assets

- [3D Models - YDS4W_MODEL-STEP](#)
- [3D Models - YDS4W_MODEL-PDF](#)
- [3D Models - YDS4W_MODEL-IGES](#)
- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_YDS_LineArt](#)
- [Sales Drawings - SD..015142-02](#)
- [Specifications - YDS4W](#)