Product specifications

Eaton 170M6763

Catalog Number: 170M6763

Fuse-link, high speed, 900 A, AC 690 V, size 3, 76 x 92 x 139 mm, aR, IEC, UL, single indicator

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M6763

UPC
051712265539

EAN
5996516020692

Product Length/Depth
168 mm

Product Height
76 mm

Product Width
95 mm

Product Weight
986 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
UL Recognized
IEC Rated

Product specifications

Interrupt rating

200 kAIC

Center-to-center distance of connections

114 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

900 A

Fuse type

US Style

FKE/115 Type K indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other

Fitted with:

Type K Indicator for micro

Fuse size

3

Voltage rating

690 V

Fuse indicator

Centre fuse status indicator

Construction size

3

Clearing (I2T)

670000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

Other

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M6763~Eaton Bussmann series high speed square body fuse

Specifications and datasheets

Eaton Specification Sheet - 170M6763

Utilization category

aR (accompanied semiconductor protection)

Watt losses

120 W

Type

Fuse

Fuse shape

Square body, center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

100000

Application

semiconductor protection

Voltage type

AC

Packaging type

Standard

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia