Product specifications

Eaton FWX-1500AH

Catalog Number: FWX-1500AH

Eaton Bussmann series FWX high speed fuse, 1500A, 200 kAIC Vac, 50 kAIC at 250 Vdc, None, High speed fuse, Blade end X blade end, Flush

General specifications

Product Name
Eaton Bussmann series high speed cylindrical fuse

Catalog Number
FWX-1500AH

UPC
051712795630

EAN
5027590021968

Product Length/Depth
76.2 mm

Product Height
76.2 mm

Product Width
66 mm

Product Weight
1938 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
UL Recognized
CSA Certified

Product specifications

Interrupt rating

50 kAIC at 250 Vdc

200 kAIC Vac

Center-to-center distance of connections

65.8 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

Flush

Amperage Rating

12 A

Fuse type

FWX-AH

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type B

Rated switching capacity

200 A

Voltage rating

250 Vac, 250 Vdc

Fuse indicator

Non Indicating

Construction size

Other

Clearing (I2T)

880000 at 250 V

Rated voltage AC

250 V

Color

None

Connection

Blade end x blade end

Mounting dimension

Other

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - FWX-1500AH

Utilization category

aR (accompanied semiconductor protection)

Watt losses

140 W

Type

High speed fuse

Fuse shape

Cylindrical, flush end

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

120000

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia