Product specifications

Eaton WSR3352

Catalog Number: WSR3352

Eaton Crouse-Hinds series Arktite WSR interlocked receptacle with enclosed disconnect switch, 30A, Three-wire, four-pole, Brass contacts, Solid door, Fused, Style 2, 7.5 HP/15 HP/20 HP, Copper-free aluminum, Spring door, 1", 240-600 Vac

General specifications

Product Name	**Catalog Number**
Eaton Crouse-Hinds series Arktite WSR interlocked receptacle with enclosed disconnect switch	WSR3352
	UPC
	782274019420
Product Length/Depth	**Product Height**
11.75 in	27.69 in
Product Width	**Product Weight**
7.25 in	36 lb

Powering Business Worldwide

Certifications and compliances

Area classification

Ordinary/Non-Hazardous Locations

Standards type

NEC/CEC

NEMA Rating

3R

4

12

Product specifications

Door style

Solid

Amperage Rating

30A

Fusing

Fused

Grounding style

Style 2

Configuration

Three-wire, four-pole

Material

Copper-free aluminum

Contact material

Brass

Voltage rating

240-600 Vac

Horsepower

7.5 hp/15 hp/20 hp

Receptacle style

Spring door

Trade size

1"

Resources

Catalogs

Arktite WSR/WSRD Interlock Receptacles catalog page

Certification reports

Arktite WSR/WSRD Interlock Receptacles with Enclosed Disconnect Switches Canadian certification

Arktite WSR/WSRD Interlock Receptacles with Enclosed Disconnect Switches UL certification

Installation instructions

IF 1315 - WSR Series Model 94 Interlock Receptacle

IF 943 - WSR Series Model 82 Interlock Receptacle

Specifications and datasheets

Eaton Specification Sheet - WSR3352

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia