Product specifications

Eaton DS6-34DSX041N0-N

Catalog Number: DS6-34DSX041N0-N

Eaton DS7 soft start controller, 10 second ramp, one start per hour, 300% CL at 40°C, XTOB040DC1 rec XTOB overload, C440 A1A045SAX rec C440 overload, 40 A, 10 hp at 200 V, 10 hp at 230 V, 30 hp at 460 V, HFD3150L max breaker

General specifications

Product Name
Eaton DS7 soft start controller

Catalog Number
DS6-34DSX041N0-N

UPC
786685313641

Product Length/Depth
5.47 in

Product Height
6.89 in

Product Width
3.66 in

Product Weight
4 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
C-Tick Compliant
CE Marked

Certifications
UL Listed
IEC 60947-4-2
EN 60947-4-2
CSA Certified

Catalog Notes
XTOB040DC1 recommended XTOB overload, C440A1A045SAX recommended C440 overload

Product specifications

Type

10 second ramp, one start per hour, 300% current limit at 40°C

Phase

Two-phase

Circuit breaker type

HFD3150L

Rating

10 hp at 200 V, 10 hp at 230 V, 30 hp at 460 V

Fuse size

150 A class RK5 max

Amperage Rating

40A

Resources

Catalogs

Eaton's Volume 6—Solid-State Motor Control

Installation instructions

DS6 series soft start controllers

Multimedia

Soft starter DS7 up to 200 A

Soft Starter DS7 up to 32 A

Soft Starter Product Family Overview

Specifications and datasheets

Eaton Specification Sheet - DS6-34DSX041N0-N

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia