Product specifications

Eaton V48M28T2216

Catalog Number: V48M28T2216

Eaton General purpose ventilated transformer, Fungus proof, AL windings, DOE 2016, NEMA 2, FR944, 220°C, 225 kVA, FI/wall mt uprt, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 225 kVA, WS61, 280B

General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
V48M28T2216

UPC
786680147289

Product Length/Depth
33.5 in

Product Height
60 in

Product Width
38 in

Product Weight
1571 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
DOE2016 Efficient

Certifications
UL Listed

Catalog Notes
10 CFR Part 431 (2016) Efficient

Physical Attributes

Coil material
Aluminum

Enclosure
NEMA 2

Frame
FR944

Insulation
220 °C

Mounting
Floor or wall, upright only

Tap size
2 at +2.5%, 4 at -2.5%

Type
Energy-efficient ventilated dry-type transformer

Wiring connection
280B

Performance Ratings

Efficiency
10 CFR Part 431-2016 (DOE 2016)

Frequency rating
60 Hz

Kva Rating
225 kVA

Primary voltage
480 V delta

Secondary Voltage
208Y/120 V

Sound Level
NEMA ST-20

Temperature rise
150 °C rise

Volt ampere rating
225 kVA

Voltage rating
480 Vac-208Y/120 Vac

Miscellaneous

Weathershield
WS61

Resources

Brochures

Eaton's high-efficiency dry-type transformers

Eaton's low-voltage dry-type distribution transformers

Specifications and datasheets

Eaton Specification Sheet - V48M28T2216



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia