Product specifications

Eaton DSD SR30420 SX178

Catalog Number: DSD SR30420 SX178

Eaton Crouse-Hinds series DSD-SR selector switch, 30A, 1.5 HP/3 HP/5 HP/7.5 HP/10 HP, Copper-free aluminum, 1, Four-pole, 2, Lockout for two position switch, handle in either position, On/Off, 600 Vac, EDS/EFS back boxes

General specifications

Product Name
Eaton Crouse-Hinds series DSD-SR selector switch

Catalog Number
DSD SR30420 SX178

UPC
662276039841

Product Length/Depth
2.38 in

Product Height
5.875 in

Product Width
3.5 in

Product Weight
1.58 lb

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class II, Division 1

Class III

NEMA Rating

3

5

12

Product specifications

Amperage Rating

30A

Voltage rating

600 Vac

Switch function

On/Off

Number Of Poles

Four-pole

Number Of Positions

2

Horsepower

1.50 hp, 3 hp, 5 hp, 7.50 hp, 10 hp

Material

Copper-free aluminum

Number of devices

1

Special features

Lockout for two position switch, handle in either position

Used with

EDS/EFS back boxes

Resources

Catalogs

DSD-SR Series Explosionproof HP Rated Selector Switch Sub-assembly catalog page

Certification reports

DSD-SR Explosionproof HP Rated Selector Switch Sub-assembly UL certification

DSD-SR Explosionproof HP Rated Selector Switch Sub-assembly Canadian certification

Specifications and datasheets

Eaton Specification Sheet - DSD SR30420 SX178



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia