Product specifications

Eaton TMCX125 1 L

Catalog Number: TMCX125 1 L

Eaton Crouse-Hinds series Terminator II TMCX cable gland,Liquid compound,Cable Range:0.87-1.39",Cable Sealing:1 (S),Metal-cladcorrugated armoured,TECK armoured,armoured barrier and tray cable,Armoured gland, Aluminum, 1-1/4" NPT

General specifications

Product Name	**Catalog Number**
Eaton Crouse-Hinds series Terminator II TMCX cable gland	TMCX125 1 L
	UPC
	662276303768
Product Length/Depth	**Product Height**
4.38 in	2.56 in
Product Width	**Product Weight**
2.56 in	1.1 lb

Powering Business Worldwide

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class II, Division 1

Class III

NEMA Rating

6P

4X

Product specifications

Protection type

Explosion-proof

Cable type

TECK armoured

Tray cable

Armoured barrier

Metal-clad with interlocked or continuously welded corrugated armoured

Gland type

Armoured

Thread Size

1-1/4"

Thread type

NPT

Cable sealing range

1 (S)

Cable range (min/max)

0.87-1.39"

Material

Aluminum

Barrier type

Liquid Compound

Resources

Brochures

Crouse-Hinds series TMCX II brochure

Crouse-Hinds series Chico LiquidSeal flyer

Catalogs

Crouse-Hinds series TMCX II catalog page

Certification reports

TMCX II Explosionproof Armoured Barrier and Non-armoured Barrier Gland Canadian certification

TMCX II Explosionproof Armoured Barrier and Non-armoured Barrier Gland UL certification

Installation instructions

IF 1647 - TMCX Terminator II Cable Gland

IF 1647B - TMCX Terminator II Cable Gland

Specifications and datasheets

Eaton Specification Sheet - TMCX125 1 L

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia