Product specifications

Eaton 13108A6517

Catalog Number: 13108A6517

Eaton Comet 18mm tubular photoelectric sensor, Perfect Prox Photoelectric Sensor, Back Ground Suppression, 6 in range, Forward Viewing, Output ON, 6.6 ft, 100 mA PNP, 250 mA NPN at 10-30 Vdc, PVC, NPN and PNP open collector, 10-30 Vdc

General specifications

Product Name	**Catalog Number**
Eaton Comet 18mm tubular photoelectric sensor	13108A6517
	UPC
	782113823508
Product Length/Depth	**Product Height**
2.6 in	0.71 in
Product Width	**Product Weight**
0.47 in	0.67 lb
Warranty	**Certifications**
3 year	UL Recognized cUL Recognized

Product specifications

Contact configuration

NPN and PNP open collector

Cord length

79.2 ft

Maximum DC current

100 mA PNP, 250 mA NPN

Operating temperature - min

-40 °F

Input voltage

10-30 Vdc

Cable type

Polyvinyl Chloride (PVC)

LED indicator

Output ON

Enclosure material

Polyurethane foam (RIM)

Type

Perfect Prox Photoelectric Sensor

Sensor type

Back ground suppression

Contact Rating

100 mA PNP, 250 mA NPN at 10-30 Vdc

Operating temperature - max

158 °F

Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13, IP69K

Protection

Auto reset short circuit

Resources

Brochures

Comet series - Photoelectric sensors

Catalogs

Eaton's Volume 8—Sensing Solutions

Product Range Catalog Sensors – products, basic information, applications

Specifications and datasheets

Eaton Specification Sheet - 13108A6517



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia