Product specifications

Eaton XTCS300L22A

Catalog Number: XTCS300L22A

Eaton XT IEC contactor, 300A, 110 Vdc 40 Hz, 250 Vdc 60 Hz, 2NO-2NC, 300A, Frame L, 140 mm, 40-60 Hz, 100, 125, 250, 300 hp 3PH 200, 230, 460, 575 V, Three-pole, S-series, Screw terminals, FVNR

General specifications

Product Name
Eaton XT IEC contactor

Catalog Number
XTCS300L22A

EAN
4015081363360

Product Length/Depth
10.5 in

Product Height
9 in

Product Width
7 in

Product Weight
15 lb

Certifications
UL Listed
CSA Certified

Product specifications

Contact configuration

2 NO, 2 NC

Coil voltage

110-250 Vdc

Series

XT IEC /S-

Type

Full voltage non-reversing contactor

HP rating - max

100, 125, 250, 300 hp (3PH @200,230,460,575 V)

Continuous ampere rating

300 A

Frequency rating

40-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

300 A

Number Of Poles

Three-pole

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Specifications and datasheets

Eaton Specification Sheet - XTCS300L22A

Global Data Sheet - XTCS300L22A

Voltage Sag Ride Through for XT IEC Contactor Frames L - N

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia