Product specifications

Eaton FCF1RN

Catalog Number: FCF1RN

Eaton Bussmann series FCF fuse, 1 A, 60 Hz, 50 Hz, 1 , CF, Black, Non-indicating, Electroless tin plated copper alloy terminal, Blade end|Class CF, 4 min at 200%, 300 kAIC at 600 V|50 kAIC at 600 Vdc, Glass filled PES, 600 V, 600 Vdc

General specifications

Product Name	**Catalog Number**
Eaton Bussmann series FCF fuse	FCF1RN
UPC	**Product Length/Depth**
051712362412	1.88 in
Product Height	**Product Width**
1.75 in	0.75 in
Product Weight	**Warranty**
0.08 lb	Not Applicable
Compliances	**Certifications**
CE Marked RoHS Compliant	UL Listed CSA Certified

Electrical rating

Amperage Rating

1 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac

50 kAIC at 600 Vdc

Response time

4 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Fast acting

Class CF

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH30N, CCP2-3-30CF

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

FCF1RN~Fast Acting CUBEFuse 1A Non-indication

Multimedia

The Power of Space

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - FCF1RN



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia