Product specifications

Eaton XDT3C15X

Catalog Number: XDT3C15X

Eaton Crouse-Hinds series XDT dry-type transformer, 60 Hz, 15 kVA, 316 stainless steel, Three-phase, 480 Vac, 240 Vac, Copper windings, Resin encapsulated

General specifications

Product Name	**Catalog Number**
Eaton Crouse-Hinds series XDT dry-type transformer	XDT3C15X
	UPC
	662276445420
Product Length/Depth	**Product Height**
23.48 in	15.55 in
Product Width	**Product Weight**
11.22 in	319 lb

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 2

NEMA Rating

4X

Product specifications

Type

Resin encapsulated

Phase

Three-phase

Primary voltage

480 Vac

Secondary Voltage

240 Vac

Frequency rating

60 Hz

Material

316 stainless steel

Special features

Copper windings

Resources

3D models

SP3D Design Package - XDT and XTT Hazardous Area Transformers

Catalogs

XDT and XTT Hazardous Area Transformers catalog page

Certification reports

XDT and XTT Hazardous Area Transformers UL certification

XDT and XTT Hazardous Area Transformers Canadian certification

Installation instructions

XDT and XTT Hazardous Area Transformers Flyer

IF XDT - XDT Series Hazardous Area Transformers

Specifications and datasheets

Eaton Specification Sheet - XDT3C15X

XDT Hazardous Area Transformers



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia