Product specifications

# Eaton CSR33542

## Catalog Number: CSR33542

Eaton Crouse-Hinds series Arktite CSR interlocked receptacle, 30A, Brass contacts, Non-fused, Style 2, 10 HP/20 HP/25 HP, Krydon fiberglass-reinforced polyester, 1", 250-600 Vac

### General specifications

| | |
|---|---|
| **Product Name** | **Catalog Number** |
| Eaton Crouse-Hinds series Arktite CSR interlocked receptacle | CSR33542 |
| | **UPC** |
| | 782274215440 |
| **Product Length/Depth** | **Product Height** |
| 7.87 in | 18.26 in |
| **Product Width** | **Product Weight** |
| 7.78 in | 16.25 lb |

## Certifications and compliances

### Area classification

Ordinary/Non-Hazardous Locations

### Standards type

NEC/CEC

### NEMA Rating

3

4

4X

12

### Ingress protection (IP) ratings

IP66

## Product specifications

### Amperage Rating

30A

### Trade size

1"

### Fusing

Non-fused

### Voltage rating

250-600 Vac

### Horsepower

10 hp/20 hp/25 hp

### Grounding style

Style 2

### Material

Krydon fiberglass-reinforced polyester

### Contact material

Brass

## Resources

### Catalogs

Arktite CSR Nonmetallic Interlock Receptacles catalog page

### Certification reports

Arktite CSR Nonmetallic Interlock Receptacles UL certification

Arktite CSR Nonmetallic Interlock Receptacles Canadian certification

### Installation instructions

IF 1439 - CSR 30A and 60A Interlocked Receptacle

IF 1440 - CSR 30A and 60A Interlocked Receptacle with Bussmann Fuses

IF 1334 - CSR Interlocked Receptacle

### Specifications and datasheets

Eaton Specification Sheet - CSR33542




Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia