Product specifications

Eaton 170M4060

Catalog Number: 170M4060

Fuse-link, high speed, 315 A, AC 690 V, DIN 1, 53 x 66 x 108 mm, aR, DIN, IEC, single indicator

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M4060

Model Code
FUSE 315A 690V 1TN/80 AR UC

UPC
051712257534

EAN
5027590451000

Product Length/Depth
245 mm

Product Height
62 mm

Product Width
142 mm

Product Weight
455 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
IEC Rated
UL Recognized

Product specifications

Interrupt rating

200 kAIC

Clearing loss

58

Center-to-center distance of connections

78 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

315 A

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other

Fuse size

1

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Top fuse status indicator

Construction size

1

Clearing (I2T)

42000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

M10

Resources

Catalogs

170M4060~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Compliance information

CE Fuse-links for the protection of semiconductor devices, Size 1 up to 900A

UKCA Fuse-links for the protection of semiconductor devices, Size 1 up to 900A

Technical data sheets

720014 DIN 43653 690V

Utilization category

aR (accompanied semiconductor protection)

Watt losses

58 W

Type

Fuse

Fuse shape

Square body, slotted center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

6200

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia