Product specifications

Eaton DG1-34385FN-C00C

Catalog Number: DG1-34385FN-C00C

Eaton PowerXL DG1 variable frequency drive460V FR7 IP00 200KW 300HP AMR

General specifications

Product Name
Eaton PowerXL DG1 variable frequency drive

Catalog Number
DG1-34385FN-C00C

UPC
786687035305

Product Length/Depth
62.5 in

Product Height
27 in

Product Width
31.5 in

Product Weight
529 lb

Warranty
Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.

Compliances
CE Marked
RoHS Compliant

Certifications
cUL Listed
UL Listed

Product specifications

Max overload
110% for 1 minute

Protection filtering
EMI and DC Choke

High overload (CT) amps
385 A

Phase
Three-phase input, three-phase output

Motor control modes
Frequency, Speed, Open-loop speed, Open-loop torque

Internal DC choke
Yes

Conformal coated boards
Yes

Low overload (VT) kW
250 kW

Enclosure
IP00

Number of slots
2 expansion slots

Communications onboard
EtherNet/IP, Modbus TCP, RS-485: Modbus RTU, BACnet MS/TP

Motor type
Inductio, PM (IPM & SPM)

Electromagnetic compatibility filter
EMC Filter

User interface
Graphical Keypad

Power consumption
200 kW

High overload (CT) kW
200 kW

Horsepower
300 hp

Resources

Application notes
Connecting drives to generator supplies

Analog I/Os

Digital I/Os

Electromagnetic compatibility (EMC)

Operating at low temperatures

Torque control

Smoke Mode and fire mode

PID controller

DG1 in pump and fan applications

Motor data and V/f curves

Real time clock and use of the timers

Dual Rating What exactly does that mean?

Starting, stopping and operation

Load balancing in multi motor applications

Catalogs
Product Range Catalog Drives Engineering

Specifications and datasheets
Eaton Specification Sheet - DG1-34385FN-C00C

Operating Temperature

-10° to 50°C

Voltage rating

460 V

Protection

Internal EMC filter, DC choke

Communication

EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU communication

Material

Coated board

Low overload (VT) hp

350 hp

Output current - max

385 A

Low overload (VT) amps

460 A

High overload (CT) hp

300 hp

Frame size

7

Output frequency range

0 - 400 Hz

Input voltage range

380 - 500 V

Recommended fuse size

600

Keypad

Included

Input frequency range

50 - 60 Hz

Software

Active energy control, quick start wizard

Torque rating

CT

Display

LCD graphical



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia