Product specifications

Eaton FWP-4G14F

Catalog Number: FWP-4G14F

Eaton Bussmann series FWP high speed fuse, 690V, 4A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end - FWP-4G14F

General specifications

Product Name
Eaton Bussmann series high speed cylindrical fuse

Catalog Number
FWP-4G14F

UPC
051712691758

EAN
5027590500838

Product Length/Depth
14 mm

Product Height
14 mm

Product Width
51 mm

Product Weight
19 g

Warranty
No warranty

Compliances
CE Marked
RoHS Compliant

Certifications
UL Recognized
IEC Rated

Product specifications

Fuse indicator
Non Indicating

Interrupt rating
200 kAIC

Construction size
14 mm x 51 mm

Clearing (I2T)
17

Connection
Ferrule end x ferrule end

Material
Ceramic

Release characteristic
Other

Amperage Rating
4 A

Frequency rating - max
62 Hz

Utilization category
gR (general purpose semiconductor protection)

Watt losses
2.94 W

Fuse type
FWP-G14F

Accessories
CH14 Modular fuse holder
FW14-PCB

Type
High speed fuse

Fuse shape
Cylindrical

Breaking capacity
200 kA

Fuse size
14 x 51 mm

Resources

Catalogs
IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information
CE High-speed, cylindrical gR fuse-links

UKCA High-speed, cylindrical gR fuse-links

Specifications and datasheets
Eaton Specification Sheet - FWP-4G14F

Technical data sheets
10468 14 x 51 mm gR cylindrical fuse links

Frequency rating - min

45 Hz

Class

Class gR

Pre arc (I2T)

5.6

Voltage rating

700 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC

Packaging type

Standard

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia