Product specifications

Eaton 14150RL04

Catalog Number: 14150RL04

Eaton OEM Prism 18mm tubular photoelectric sensor, Right Angle, dist 15 Ft., Iso SS Relay, 80 mA at 132 Vac/110 mA at 132Vdc, 4 Pin Dual Key Micro, 20–132 Vac/15-30 Vdc input

General specifications

Product Name
Eaton OEM Prism 18mm tubular photoelectric sensor

Catalog Number
14150RL04

UPC
782113011080

Product Length/Depth
0.47 in

Product Height
2.75 in

Product Width
0.71 in

Product Weight
0.1313 lb

Warranty
3 year

Compliances
CE Marked
Contact Manufacturer

Certifications
UL Recognized
cUL Recognized

Catalog Notes
For complete system; order sensor and retroreflector. Retroreflector not included

Product specifications

Contact configuration

Isolated solid state relay

Switch type

Photoelectric

Cord length

8 in

Maximum AC current

80 mA

Maximum DC current

110 mA

Operating temperature - min

-13 °F

Input voltage

20-132 Vac, 15-30 Vdc

Connection

4-pin dual key micro connector

Cable type

Polyvinyl Chloride (PVC)

LED indicator

Output status: red

Enclosure material

Lens: polycarbonate
Cable jacket: PVC
Body: structural polyurethane foam

Operating mode

Non polarized retroreflective

Sensor type

Retroreflective

Contact Rating

80 mA at 132 Vac / 110 mA at 132Vdc

Operating temperature - max

131 °F

Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13

Protection

Resources

Catalogs

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - 14150RL04

Current limited for loads less than 32 Vac/dc

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia