Product specifications

Eaton EMI104-10

Catalog Number: EMI104-10

Eaton Metered Input rack PDU, 0U, L6-30P input, 5.76 kW max, 200-240V, 24A, 10 ft cord, Single-phase, Outlets: (36) C13 Outlet grip, (6) C19 Outlet grip

General specifications

Product Name	**Catalog Number**
Eaton metered input rack PDU	EMI104-10
UPC	**Product Length/Depth**
743172050458	2.05 in
Product Height	**Product Width**
66.5 in	2.1 in
Product Weight	**Warranty**
15.54 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Product specifications

Number of Outputs C13
36

Special features
Voltage monitoring

Number of Outputs C19
6

Outlet control
No

Switchable
No

Cord length
10 ft

Phase
Single-phase

Input voltage
200-240V

Color
Black

Wattage
5.76 kW max

Form factor
0U (Vertical)

Mounting direction
Vertical

Amperage Rating
24A

Input connection
L6-30P

Outlets
(36) C13 Outlet grip, (6) C19 Outlet grip

Series
Metered Input

Type
PDU

Fitted with:

Resources

Brochures
Eaton ePDU G3 brochure

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU G3 Metered Input EMI104-10 technical drawing

Eaton Metered Input PDU Visio stencils

Service & troubleshooting
ePDU G3 firmware and MIBs

EMI104-10 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMI104-10

User guides
Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 operations manual

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 installation and connectivity quick start guide

Warranty guides
Eaton limited warranty for rackmount PDUs

Ampere Meter

Frequency rating

50-60 Hz

Operating Temperature

0° to 60°C (32° to 140°F)

Ethernet interface

Yes

Circuit breaker

(2) 20A

Serial interface

RS-232

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia