Product specifications

Eaton TPC12F-A-CB

Catalog Number: TPC12F-A-CB

Eaton Basic rack PDU, 1U, 5-15P input, 1.44 kW max, 110-125V, 12A, 9 ft cord, Single-phase, Circuit breaker, EMI/RFI filter, TAA compliant, Outlets: (12) 5-15R

General specifications

Product Name	**Catalog Number**
Eaton basic rack PDU	TPC12F-A-CB
UPC	**Product Length/Depth**
786685288932	19 in
Product Height	**Product Width**
1.7 in	4 in
Product Weight	**Warranty**
8 lb	3 year
Compliances	**Certifications**
Contact Manufacturer TAA Compliant	UL Listed

Product specifications

Outlet control
No

Cord length
9 ft

Phase
Single-phase

Input voltage
110-125V

Color
Black

Wattage
1.44 kW max

Form factor
1U

Mounting direction
Horizontal

Amperage Rating
12A

Input connection
5-15P

Outlets
(12) 5-15R

Type
PDU

Frequency rating
50-60 Hz

Operating Temperature
0° to 60°C (32° to 140°F)

Number of Outputs 5-15R
12

Circuit breaker
1P 15A

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Eaton RoHS declaration of conformity: ePDU G3

Drawings
Eaton basic PDU TPC12F-A-CB tech drawing

Eaton PDU TPC12F-A-CB technical drawing

Installation instructions
Eaton ePDU G3 troubleshooting guide

Specifications and datasheets
Eaton Specification Sheet - TPC12F-A-CB

User guides
Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 operations manual

Eaton ePDU G3 installation and connectivity quick start

Eaton ePDU G3 replace and configure eNMC module



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia