Product specifications

Eaton C25DRD3301T-GL

Catalog Number: C25DRD3301T-GL

Eaton definite purpose contactor, Quick, 40A, 24 Vac, 50/60 Hz, Open with DIN rail mounting adapter, 15-50A, two- and three-pole, 40A, Contactor, Three-pole, 50A, Box lugs (posidrive setscrew) and quick connect terminals , Non-reversing

General specifications

Product Name
Eaton definite purpose contactor

Catalog Number
C25DRD3301T-GL

UPC
786685702728

Product Length/Depth
3.35 in

Product Height
3.75 in

Product Width
2.4 in

Product Weight
1.19 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
1 year

Compliances
RoHS Compliant
CE Marked

Certifications
CSA Certified
UL Listed file E1491 (Guide Number NLDX2)
UL Recognized

Product specifications

Options
Global listed

Inductive full load
30 A

Auxiliary contacts
Pressure plate quick connect (side-by-side)

Connection
Quick

Enclosure
Open with DIN rail mounting adapter

Amperage Rating
30A

Number Of Poles
Three-pole

Coil
24 Vac, 50/60 Hz

Frame size
15-50 A, two-pole and three-pole

Accessories
DIN rail mounting adapter

Coil voltage
24 Vdc

Series
D1

Type
Non-reversing

Model
Contactor

Terminals
Screw/pressure plate and quick connect terminals (side-by-side)

Resistive load
40 A

Resources

Catalogs
Eaton's Volume 5—Motor Control and Protection

Drawings
C25DRD3_1 2D PDF

C25DRD3_1 AutoCAD 2D Footprint

C25DRD3_1 AutoCAD 2D Footprint (mm)

C25DRD3_1 3D Model Xchange

C25DRD3_1 3D Inventor

C25DRD3_1 2D Drawing Xchange

Specifications and datasheets
Eaton Specification Sheet - C25DRD3301T-GL

Warranty guides
Selling Policy 25-000 - Distribution and Control Products and Services



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia