Product specifications

Eaton DCU2064URM

Catalog Number: DCU2064URM

Eaton heavy duty DC disconnect,DC disconnect/ungrounded system,200A,NEMA 3R,Painted galvanized steel,Non-fusible,Ungrounded,LC: In 300 MCM-#6 out 300 MCM-#6. SR: in 300 MCM-#6 out 300 MCM-#6. EG: in #4-#14 AWG out 1/0-#14,600 Vdc,2

General specifications

Product Name
Eaton heavy duty DC disconnect

Catalog Number
DCU2064URM

UPC
786685625140

Product Length/Depth
37.5 in

Product Height
11.5 in

Product Width
19 in

Product Weight
45 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL 98B
NEC 690 per UL 1741

Product specifications

Maximum voltage
600 VDC

Switch type
Heavy duty

Ground
Ungrounded

Fuse configuration
Non-fusible

Enclosure
NEMA 3R

Amperage Rating
200 A

Enclosure material
Painted galvanized steel

Series
DC Photovoltaic Applications

Type
DC disconnect/ungrounded system

System voltage
600 VDC per pole

NEMA rating
NEMA 3R

Main lug wire size
LC: In 300 kcmil-#6 out 300 kcmil-#6. SR: in 300 kcmil-#6 out 300 kcmil-#6. EG: in #4-#14 AWG out 1/0-#14

Number of circuits
2

Voltage rating
600 VDC

Protection
Non-fusible

Application
Solar

Resources

Brochures
DC disconnects for grounded and ungrounded photovoltaic installations

Multimedia
Double Up on Safety

Switching Devices Flex Center

Specifications and datasheets
Eaton Specification Sheet - DCU2064URM



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia