Product specifications

Eaton EMI317-10

Catalog Number: EMI317-10

Eaton Metered Input rack PDU, 0U, 48A, 309-460P9 input, 17.3 kW max, 200-240V, 6 ft cord, 3-ph, Outlets: (9) C13, (12) C19

General specifications

Product Name	**Catalog Number**
Eaton metered input rack PDU	EMI317-10
UPC	**Product Length/Depth**
786685974651	66.5 in
Product Height	**Product Width**
2.1 in	2.05 in
Product Weight	**Warranty**
14 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Product specifications

Number of Outputs C13

9

Number of Outputs C19

12

Outlet control

No

Switchable

No

Cord length

10 ft

Phase

Three-phase

Input voltage

200-240V

Color

Black

Wattage

17.3 kW max

Form factor

0U (Vertical)

Mounting direction

Vertical

Amperage Rating

48A

Input connection

309-460P9

Outlets

(9) C13, (12) C19

Series

Metered Input

Type

PDU

Fitted with:

Ampere Meter

Frequency rating

Resources

Certification reports

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings

Eaton ePDU G3 Metered Input EMI317-10 technical drawing

Eaton PDU EMI317-10 technical drawing

Service & troubleshooting

EMI317-10 eNMC replacement configuration file

Specifications and datasheets

Eaton Specification Sheet - EMI317-10

User guides

Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 operations manual

50-60 Hz

Operating Temperature

0° to 60°C (32° to 140°F)

Ethernet interface

Yes

Circuit breaker

(6) 20A

Serial interface

RS-232

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia