Product specifications

Eaton 170M7636



Photo is representative

Catalog Number: 170M7636

Fuse-link, high speed, 1500 A, AC 1000 V, 200 kA, size 4, 105 x 120 x 95 mm, aR, IEC, type K indicator

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M7636

UPC
051712683562

EAN
5996516021736

Product Length/Depth
95 mm

Product Height
105 mm

Product Width
120 mm

Product Weight
2729 g

Compliances
CE
RoHS Compliant
EAC

Certifications
IEC 60269-4

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

1500 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

4

Rated voltage AC

1000 V

Center-to-center distance of connections

87.6 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

3600000 at 1000 V

Watt losses

250 W

Pre arc (I2T)

600000

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Technical data sheets

170M Size 4 Flush end fuses 1000 VAC (IEC and IEC/UL)

Color

None

Interrupt rating

200 kAIC

Construction size

4

Mounting method

Flush

Voltage rating

1000 V (IEC)

Fuse type

Flush end

BKN/95 Type K Indicator

Fuse system (according to IEC 60269)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia