Specifications



Photo is representative

Eaton XTRM10A22TD

XT IEC Miniature Control Relay, Screw terminals, 45 mm - mini Frame size, 2NO-2NC contact configuration, 24 Vdc coil, 10A conventional thermal rating, 6A at 220/230/240V; 3A at 380/400/415V rated operational voltage

General specifications	
PRODUCT NAME	Eaton XT IEC control relay
CATALOG NUMBER	XTRM10A22TD
EAN	4015080100423
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	2.5 in
PRODUCT WEIGHT	0.3 lb
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Control relay

Powering Business Worldwide

Product specifications

TYPE	Control relay
FRAME SIZE	45 mm - mini
COIL VOLTAGE	24 Vdc
CONTACT CONFIGURATION	2 NO, 2 NC

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTRM10A22TD

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.