Product specifications

Eaton BK/NON-30

Catalog Number: BK/NON-30

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 30 A, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 125 Vac/dc, Bulk, 100, 250 V, 125 Vdc



General specifications

Product Name	**Catalog Number**
Eaton Bussmann series NON fuse	BK/NON-30
UPC	**Product Length/Depth**
051712555197	2 in
Product Height	**Product Width**
0.56 in	0.56 in
Product Weight	**Warranty**
0.35 lb	Not Applicable
Compliances	**Catalog Notes**
Not Applicable	Bulk

Powering Business Worldwide

Electrical rating

Amperage Rating

30 A

Interrupt rating

50 kAIC at 125 Vac/dc

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

Bulk

General information

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

100

Special features

Rejection style

Resources

Catalogs

BK/NON-30~BK-NON-30~BUSS ONE TIME FUSE

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - BK/NON-30

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia