Product specifications

Eaton 170M7066



Catalog Number: 170M7066

Fuse-link, high speed, 4000 A, AC 600 V, 200 kA, size 4, 67 x 105 x 105 mm, aR, IEC, single indicator

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M7066

UPC
051712266505

EAN
5027590463560

Product Length/Depth
41.798 mm

Product Height
53.01 mm

Product Width
137.998 mm

Product Weight
746 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
IEC Rated
UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

4000 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Temperature rating

>60°C

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

4

Rated voltage AC

600 V

Center-to-center distance of connections

66.6 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

28000000 at 500 V

Watt losses

355 W

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

170M7066~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

4700000

Color

None

Interrupt rating

200 kAIC

Construction size

4

Mounting method

Flush

Packaging type

Standard

Voltage rating

600 V

Fuse type

Flush end

B/65 Visual indicator

Fuse system (according to IEC 60269)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia