Specifications



Photo is representative

Eaton XTOM006AC1

Eaton XT IEC control relay, XT IEC Miniature Overload Relay, 4-6A overload range, 45 mm - mini Frame size, 1NO-1NC contact configuration, Direct mounting, 10A trip type

General specifications	
PRODUCT NAME	Eaton XT IEC control relay
CATALOG NUMBER	XTOM006AC1
EAN	4015080145653
PRODUCT LENGTH/DEPTH	1.85 in
PRODUCT HEIGHT	2.36 in
PRODUCT WIDTH	2.56 in
PRODUCT WEIGHT	0.2 lb
COMPLIANCES	RoHS Compliant ATEX Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted firectly to contactor.
PRODUCT TYPE	Control relay

Powering Business Worldwide

Product specifications

TYPE	Control relay

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOM006AC1

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.