Product specifications

Eaton 170M1313

Catalog Number: 170M1313

Fuse-link, high speed, 40 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC



Photo is representative

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M1313

Model Code
FUSE 40A 690V 000U/80 GR UC

UPC
051712216494

EAN
5027590440745

Product Length/Depth
105 mm

Product Height
46 mm

Product Width
300 mm

Product Weight
139 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
IEC Rated
UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

40 A

Breaking capacity

200 kA

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Utilization category

gR (general purpose semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Center-to-center distance of connections

76.7 mm

Current type

AC

Mounting dimension

M8

Class

Class gR

Clearing (I2T)

460 at 660 V

Watt losses

12 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

170M1313~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M size 000 10A to 315A

UKCA 170M size 000 10A to 315A

Pre arc (I2T)

69

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

U/80 Without indicator

Bolted tag

Fuse system (according to IEC 60269)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia