Product specifications

Eaton 170M2667

Catalog Number: 170M2667

Fuse-link, high speed, 200 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs



General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M2667

Model Code
FUSE 200A 690V 00TN/80 AR UR

UPC
051712792875

EAN
5027590442442

Product Length/Depth
100 mm

Product Height
67 mm

Product Width
30 mm

Product Weight
224.3333333 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
UL Recognized
IEC Rated

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

200 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

23000 at 660 V

Watt losses

35 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA 170M Size 00, rated 690 Vac, up to 400A

CE 170M Size 00, rated 690 Vac, up to 400A

Pre arc (I2T)

3400

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

00

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia