Product specifications

Eaton 170M2669



Photo is representative

Catalog Number: 170M2669

Fuse-link, high speed, 315 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M2669

UPC
051712799195

EAN
5027590442466

Product Length/Depth
98 mm

Product Height
51 mm

Product Width
28 mm

Product Weight
211.833 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC Rated
UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

315 A

Breaking capacity

200 kA

Fuse indicator

Other

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Current type

AC

Class

Class aR

Clearing (I2T)

68500 at 660 V

Watt losses

55 W

Fuse shape

Square body, slotted offset bolted tags

Pre arc (I2T)

10000

Color

None

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M Size 00, rated 690 Vac, up to 400A

UKCA 170M Size 00, rated 690 Vac, up to 400A

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

Other

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia