Specifications



Photo is representative

Eaton XTRE10B22C

XT IEC Control Relay, Screw terminals, 45 mm - standard Frame size, 2NO-2NC contact configuration, 415V 50 Hz, 480V 60 Hz coil, 10A conventional thermal rating, 6A at 220/230/240V; 4A at 380/400/415V rated operational voltage

General specifications	
PRODUCT NAME	Eaton XT IEC control relay
CATALOG NUMBER	XTRE10B22C
EAN	4015082764029
PRODUCT LENGTH/DEPTH	1.81 in
PRODUCT HEIGHT	3.07 in
PRODUCT WIDTH	2.76 in
PRODUCT WEIGHT	0.5 lb
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Control relay

Powering Business Worldwide

Product specifications

CONVENTIONAL THERMAL CURRENT	10A
TYPE	Control relay
FRAME SIZE	45 mm - standard
COIL	415-480 Vac, 50/60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
TERMINALS	Screw terminals
RATED OPERATIONAL CURRENT	6 A at 220/230/240 V 4 A at 380/400/415 V

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTRE10B22C

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.