Product specifications

Eaton FWP-4A14F

Catalog Number: FWP-4A14F

Eaton Bussmann series FWP high speed fuse, 700V (UL), 4A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



Photo is representative

General specifications

Product Name
Eaton Bussmann series high speed cylindrical fuse

Catalog Number
FWP-4A14F

UPC
051712795128

EAN
5027590500814

Product Length/Depth
52 mm

Product Height
15 mm

Product Width
15 mm

Product Weight
20.4 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
CSA Certified
UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

4 A

Accessories

CH14 Modular fuse holder

FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

0.23

Watt losses

3 W

Fuse shape

Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720025 FWP

0.1

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14F

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia