Specifications

Eaton PV-250ANH2-B

Eaton Bussmann series Fuse-link, high speed, 250 A, DC 1000 V, NH2, gPV, UL PV, UL, IEC, dual indicator, bolted tag

General specifications	
PRODUCT NAME	Eaton Bussmann series photovoltaic fuses
CATALOG NUMBER	PV-250ANH2-B
UPC	051712531672
EAN	5027590505888
PRODUCT LENGTH/DEPTH	54 mm
PRODUCT HEIGHT	61 mm
PRODUCT WIDTH	150 mm
PRODUCT WEIGHT	434 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60269 UL Listed CSA Certified

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	250 A
VOLTAGE RATING	1000 Vdc
INTERRUPT RATING	50 kAIC
CLASS	Class gPV
PRE ARC (I2T)	17000
WATT LOSSES	38 W

Product specifications

APPLICATION	Photovoltaic systems, inverters ,Photovoltaic array combiners and disconnects
FUSE TYPE	PV-ANH2-B
FUSE INDICATOR	Combination fuse status indicator
FUSE SIZE	NH2
FITTED WITH:	Blade with bolt holes

Compatible fuse holder

SUITABLE FOR	SD2-D-PV NH Fuse base

Resources

CATALOGS	eaton-bussmann-series-photovoltaic-fuses-catalogue-ca135004en.pdf
DECLARATIONS OF CONFORMITY	CE Square-bodied PV fuse-links UKCA Square-bodied PV fuse-links
MCAD MODEL	eaton-solar-fuses-mcad-3d-models-pv-200-250a-nh2-b.stp
MULTIMEDIA	Eaton Bussmann - Products for sustainable energy
PEP ECO-PASSPORT	eaton-high-speed-photovoltaic-fuse-declaration-of-conformity-eu250023en.pdf
TECHNICAL DATA SHEETS	720133 NH photovoltaic fuse links

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.