Product specifications

Eaton C25DRD330T

Catalog Number: C25DRD330T

Eaton definite purpose contactor, DIN rail mounting adapter, Quick, 50A, Quick connect (vertical in-line), 24 Vdc, Open with DIN rail mounting adapter, 15-50A, 2P and 3P, 50A, Contactor, 2P, Global listed, D1, Box lugs (posidrive setscrew),



General specifications

Product Name	**Catalog Number**
Eaton definite purpose contactor	C25DRD330T
UPC	**Product Length/Depth**
782116483815	3.35 in
Product Height	**Product Width**
3.75 in	2.4 in
Product Weight	**Warranty**
1.19 lb	1 year
Compliances	**Certifications**
RoHS Compliant	CSA Certified UL Recognized UL Listed file E1491 (Guide Number NLDX2)

Powering Business Worldwide

Product specifications

Options
Global listed

Inductive full load
30 A

Connection
Quick

Enclosure
Open with DIN rail mounting adapter

Amperage Rating
30A

Number Of Poles
Two-pole

Coil
24 Vac, 50/60 Hz

Frame size
15-50 A, two-pole and three-pole

Coil voltage
110-120 Vac, 50/60 Hz

Series
D1

Type
Non-reversing

Model
Contactor

Terminals
Box lugs (posidrive setscrew)

Resistive load
40 A

Resources

Catalogs
Eaton's Volume 5—Motor Control and Protection

Drawings
C25DRD3 2D Drawing Xchange

C25DRD3 3D Model Xchange

C25DRD3 AutoCAD 2D Footprint

C25DRD3 AutoCAD 2D Footprint (mm)

C25DRD3 2D PDF

C25DRD3 3D Inventor

Specifications and datasheets
Eaton Specification Sheet - C25DRD330T



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia