Product specifications

Eaton V24M28T7516

Catalog Number: V24M28T7516

Eaton General purpose ventilated transformer, Aluminum windings, NEMA 2, FR942, 60 Hz, 220°C, 75 kVA, Three-phase, 240 Delta V, 208Y/120 Vac, NEMA ST-20, 150°C, 75 kVA, 240 Vac-208Y/120 Vac, WS59, 280C, DOE 2016



Photo is representative

General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
V24M28T7516

UPC
786680175565

Product Length/Depth
24 in

Product Height
43 in

Product Width
30.5 in

Product Weight
593 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL Listed

Catalog Notes
10 CFR Part 431 (2016) Efficient

Powering Business Worldwide

Physical Attributes

Coil material
Aluminum

Enclosure
NEMA 2

Frame
FR942

Insulation
220 °C

Material
Al windings

Mounting
Floor or wall, upright only

Tap size
2 at +2.5%, 4 at -2.5%

Type
Energy-efficient ventilated type DT-3 transformer

Wiring connection
280C

Performance Ratings

Efficiency
10 CFR Part 431-2016 (DOE 2016)

Frequency rating
60 Hz

Kva Rating
75 kVA

Primary voltage
240 V

Secondary Voltage
208Y/120 V

Sound Level
NEMA ST-20

Temperature rise
150 °C rise

Volt ampere rating
75 kVA

Voltage rating
240 Vac-208Y/120 Vac

Miscellaneous

Weathershield
WS59

Resources

Brochures

Eaton's low-voltage dry-type distribution transformers

Eaton's high-efficiency dry-type transformers

Specifications and datasheets

Eaton Specification Sheet - V24M28T7516



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia